Estate

EN

General information

Products & colors

Sub-collection details

Technical performance

Installation guidelines

Environmental & certifications

General information

collection	Estate
material	Engineered Hardwood
species	European White Oak
veneer	3.0 mm Oak
core	Multi-layered Engineered
texture	Smoked & Light Wire-brushed
finish	UV
warranty	35 Years Residential

Featured products

Stone Tile Name	Dimensions	Grade	Texture
Colonial Plank	7-1/2" x 3/4" x RL	Select and Better (AB)	Smoked & Light Wire-brushed
Colonial Herringbone	6" x 3/4" x 36"	Select and Better (AB)	Smoked & Light Wire-brushed
Georgian Plank	7-1/2" x 3/4" x RL	Select (ABC)	Smoked & Light Wire-brushed
Georgian Herringbone	5" x 3/4" x 24"	Select (ABC)	Smoked & Light Wire-brushed
Heritage Plank	7-1/2" x 3/4" x RL	Select and Better (AB)	Smoked & Light Wire-brushed
Heritage Herringbone	6" x 3/4" x 36"	Select and Better (AB)	Smoked & Light Wire-brushed
Landmark Plank	7-1/2" x 3/4" x RL	Select (ABC)	Smoked & Light Wire-brushed
Landmark Herringbone	5" x 3/4" x 24"	Select (ABC)	Smoked & Light Wire-brushed

Technical performance

PLANK — DIMENSIONS & CONSTRUCTION

Total Thickness	3/4" (19 mm)
Veneer Thickness	3.0 mm European White Oak
Width	7-1/2" (190 mm)
Length	Random Length (RL)
Construction	Multi-layered Engineered
Texture	Smoked & Light Wire-brushed
Finish	UV
Janka Hardness	1,360 lbf (European White Oak)

HERRINGBONE — DIMENSIONS & CONSTRUCTION

Total Thickness	3/4" (19 mm)
Veneer Thickness	3.0 mm European White Oak
Width	6" (152 mm) — Colonial & Heritage 5" (127 mm) — Georgian & Landmark
Length	36" (914 mm) — Colonial & Heritage 24" (609 mm) — Georgian & Landmark
Construction	Multi-layered Engineered
Texture	Smoked & Light Wire-brushed
Finish	UV
Janka Hardness	1,360 lbf (European White Oak)

COLOR SPECIFICATIONS

Colors	Grade	Texture
Colonial Plank	Select and Better (AB)	Smoked & Light Wire-brushed
Colonial Herringbone	Select and Better (AB)	Smoked & Light Wire-brushed
Heritage Plank	Select and Better (AB)	Smoked & Light Wire-brushed
Heritage Herringbone	Select and Better (AB)	Smoked & Light Wire-brushed
Georgian Plank	Select (ABC)	Smoked & Light Wire-brushed
Georgian Herringbone	Select (ABC)	Smoked & Light Wire-brushed
Landmark Plank	Select (ABC)	Smoked & Light Wire-brushed
Landmark Herringbone	Select (ABC)	Smoked & Light Wire-brushed

Installation guidelines

use	Residential floors (on, above, or below grade)
installation methods	Nail-down (with glue assist for widths >5") Glue-down
subfloor — concrete	≤4% moisture content, 75% RH max; minimum 60-day cure before testing
subfloor — plywood	≤12% moisture content; structurally sound, level, and clean
acclimation	3–5 days before installation
expansion gap	Plank width + 3/4" around perimeter
environment	18–27°C (65–75°F), 35–55% RH
nailing specs	16-gauge cleats or 2" nails; every 4–6" and 1–2" at both ends
glue-down specs	Hold trowel at 45°; double gluing recommended; 12 mm expansion from wall; no traffic for 24 hours

Note: Installation methods vary depending on design. Contact your Stone Tile consultant for additional information.

Disclaimer: The installation guidelines provided are the manufacturer’s recommendations only. Stone Tile is not responsible for the installation of this product. Always consult a qualified installer and follow all applicable building codes.

Environmental & certifications

FloorScore	Certified (SCS-EC10.3-2014 v4.1)
GREENGUARD	Gold Certified (UL 2818)
TVOC	≤0.5 mg/m³
California Section 01350	Compliant (CDPH/EHLB v1.2-2017)
VOC Emissions	Low-emitting material