# Taj Mahal

EN

General information

Featured products

Technical performance

Installation & care

Environmental & certifications

# General information

| | |
|---|---|
| Collection | Taj Mahal |
| Material | Natural stone (quartzite) |
| Look | Warm, natural, timeless |
| Colour | White (warm white with soft taupe and gold veining) |
| Surface finish | Honed |
| Edge | Micro-bevel |
| Application | Interior floors and walls, including shower floors and walls |
| Shade variation | As a natural stone, colour and veining vary from tile to tile |
| Origin | Quarried in Brazil |
| Nominal thickness | 3/8" (10 mm) |

# Featured products

| Colour | Finish | Edge |
| --- | --- | --- |
| **White** | Honed | Micro-bevel |

**SIZES**

| Size (imperial) | Size (metric) | Thickness |
| --- | --- | --- |
| **24" x 48"** | 610 x 1219 mm | 3/8" (10 mm) |

# Technical performance

Slip resistance (DCOF, ANSI A326.3, wet): 0.60, suitable for interior floors that get wet, including shower floors. Taj Mahal is a natural quartzite. Because natural stone varies from block to block, other measured performance values such as water absorption, frost resistance and breaking strength are not currently published for this collection.

For project-specific requirements, contact your Stone Tile consultant.

# Installation & care

| | |
|---|---|
| Application | Interior floors and walls, including shower floors and walls |
| Exterior use | Not recommended; supplied at 3/8" (10 mm) nominal thickness for interior applications |
| Installation method | Thin-set method using a white, non-staining polymer-modified mortar suited to large-format natural stone, over a sound, clean, flat, cured substrate |
| Large format | Use a mortar rated for large-format tile and stone; back-butter each tile to achieve a minimum 95% mortar contact per TTMAC (Canada) / TCNA (US) guidelines |
| Wet areas | Install over a waterproofing membrane per TTMAC (Canada) / TCNA (US) guidelines |
| Sealing | Natural stone is porous; apply a penetrating stone sealer before grouting and periodically thereafter |
| Movement joints | Provide movement (expansion) joints per TTMAC (Canada) / TCNA (US) guidelines |
| Maintenance | Clean with a pH-neutral stone cleaner; avoid acidic or abrasive cleaners |

*Note: Installation methods vary depending on design. Contact your Stone Tile consultant for additional information.*

*Disclaimer: The installation guidelines provided are the manufacturer's recommendations only. Stone Tile is not responsible for the installation of this product. Always consult a qualified installer and follow all applicable building codes.*

# Environmental & certifications

Environmental and certification documentation is not currently published for this collection. For project-specific certification requests, contact your Stone Tile consultant.